(19) World Intellectual Property Organization
International Bureau





(43) International Publication Date 2 October 2003 (02.10.2003)

PCT

(10) International Publication Number WO 03/079946 A2

(51) International Patent Classification7:

A61F 13/15

(21) International Application Number: PCT/US03/04729

(22) International Filing Date: 19 February 2003 (19.02.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/366,593

21 March 2002 (21.03.2002) US

- (71) Applicant (for all designated States except US): DOW GLOBAL TECHNOLOGIES INC. [US/US]; Washington Street, 1790 Building, Midland, MI 48674 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BUCHHOLZ, Fredric, L. [US/US]; 256 East Youngs Court, Midland, MI 48640 (US). ALLAN, David, S. [US/US]; 5402 Nakoma Drive, Midland, MI 48640 (US). WEIR, Joseph, L. [US/US]; 1009 Scott Street, Midland, MI 48640 (US).

- (74) Agent: HAYHURST, Paul, D.; The Dow Chemical Company, Intellectual Property, P.O. Box 1967, Midland, MI 48641-1967 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

 without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: DESIGNING DRY AND POROUS ABSORBENT COMPOSITES CONTAINING SUPER-ABSORBENT POLYMERS

Composite pads varying in sap content pressure sensitivity



(57) Abstract: Super-absorbent polymer composites and a method for designing the composites are presented. A target weight of aqueous liquid to be absorbed is used in conjunction with a dryness quality value and, optionally, a porosity quality value to define types and masses of both super-absorbent polymer and a substruction meshwork which are intermixed to provide a composite which optimally minimizes free liquid and provides sustained tactile dryness after the targeted weight of aqueous liquid has been absorbed. In one form of the invention, the super-absorbent polymer and/or absorption composite derive from the use of computer-implemented determination of the absorption design-instance parameters.



03/079946 A2